

Appl. No. 10/820,500
Reply to Office action of December 26, 2007

Amendments to the Claims

The listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

5

Claims 1-16 (Cancelled)

Claim 17 (Currently Amended): A clock generating circuit, comprising:

- 10 a clock generator for receiving a reference clock signal and thereby generating an output clock signal; and
- a spread spectrum control circuit, coupled to the clock generator, for generating a modulated clock signal with frequency variation according to the output clock signal and a modulation value, comprising:
- 15 a modulation value generating circuit for outputting the modulation value; and
- a frequency control circuit, coupled to the clock generator and the modulation value generating circuit, for generating the modulated clock signal according to the output clock signal and the modulation value with which an average frequency of the modulated clock signal varies;
- 20 wherein the modulation value varies with time in a predetermined manner so as to force the average frequency of the modulated clock signal to change up and down over time, the clock generator operates in a way being independent of the spread spectrum control circuit when the average frequency of the modulated clock signal changes up and down over time, and the output clock signal generated by the clock generator and the modulated signal generated by the
- 25 spread spectrum control circuit are separate signals and the modulation value varies with time in a predetermined manner so as to force the average frequency of the modulated clock signal to change up and down over time.

30 Claim 18 (Previously Presented): The clock generating circuit of claim 17, wherein the predetermined manner represents that the modulation value increases

Appl. No. 10/820,500
Reply to Office action of December 26, 2007

progressively in a first period of time and then decreases progressively in a second period of time so as to force the average frequency of the modulated clock signal to change over time.

- 5 Claim 19 (Previously Presented): The clock generating circuit of claim 17, wherein the modulation value generating circuit outputs the modulation value according to at least one of an external control and the average frequency of the modulated clock signal.
- 10 Claim 20 (Previously Presented): The clock generating circuit of claim 17, wherein the spread spectrum control circuit further comprises:
a timing control circuit, coupled between the modulation value generating circuit and the frequency control circuit, for providing a frequency control value for the frequency control circuit according the modulation value after a
15 predetermined period of time such that the average frequency of the modulated clock signal changes in accordance with the frequency control value after the predetermined period of time.
- 20 Claim 21 (Previously Presented): The clock generating circuit of claim 20, wherein the timing control circuit is a delta-sigma modulator.
- 25 Claim 22 (Previously Presented): The clock generating circuit of claim 17, wherein the clock generator is a multi-phase clock generator for generating the output clock signal including a plurality of oscillation clock signals having a same frequency but different phases.
- 30 Claim 23 (Previously Presented): The clock generating circuit of claim 22, wherein the frequency control circuit comprises:
a phase interpolator, coupled to the clock generator, for generating a plurality of interpolation signals according to at least two of the oscillation clock signals;

Appl. No. 10/820,500
Reply to Office action of December 26, 2007

and

a phase selector, coupled to the phase interpolator and the modulation value
generating circuit, for receiving the plurality of interpolation signals and
outputting one of them as the modulated clock signal according to the
5 modulation value,

Claim 24 (Previously Presented): The clock generating circuit of claim 22, wherein
the frequency control circuit comprises:

a phase selector, coupled to the clock generator, for outputting at least two of the
10 oscillation clock signals as selection signals; and
a phase interpolator, coupled to the phase selector, for generating the modulated
clock signal according to the selection signals;
wherein at least one of the phase selector and the phase interpolator operates
according to the modulation value.

Claim 25 (Currently Amended): A clock generating method, comprising:

generating an output clock signal according to a reference clock signal; and
executing a spread spectrum control step for generating a modulated clock signal
with frequency variation according to the output clock signal and a modulation
20 value, the spread spectrum control step comprising:
generating the modulation value; and
generating the modulated clock signal according to the output clock signal and
the modulation value with which an average frequency of the modulated
clock signal varies;

25 wherein the modulation value varies with time in a predetermined manner so as
to force the average frequency of the modulated clock signal to change up and
down over time, the output clock signal is generated in a way being independent
of the spread spectrum control step when the average frequency of the modulated
clock signal changes up and down, and the output clock signal and the modulated
30 clock signal are separate signals ~~the modulation value varies with time in a~~

Appl. No. 10/820,500

Reply to Office action of December 26, 2007

~~predetermined manner so as to force the average frequency of the modulated clock signal to change up and down over time.~~

5 Claim 26 (Previously Presented): The clock generating method of claim 25, wherein the predetermined manner represents that the modulation value increases progressively in a first period of time and then decreases progressively in a second period of time so as to force the average frequency of the modulated clock signal to change over time.

10 Claim 27 (Previously Presented): The clock generating method of claim 25, wherein the step of generating the modulation value is executed according to at least one of an external control and the average frequency of the modulated clock signal.

15 Claim 28 (Previously Presented): The clock generating method of claim 25, wherein the spread spectrum control step further comprises:
generating a frequency control value according the modulation value after a predetermined period of time such that the average frequency of the modulated clock signal changes in accordance with the frequency control value after the predetermined period of time.

20 Claim 29 (Previously Presented): The clock generating method of claim 25, wherein the output clock signal includes a plurality of oscillation clock signals having a same frequency but different phases.

25 Claim 30 (Previously Presented): The clock generating method of claim 29, wherein the step of generating the modulated clock signal comprises:
generating a plurality of interpolation signals according to at least two of the oscillation clock signals; and
receiving the plurality of interpolation signals and outputting one of them as the
30 modulated clock signal according to the modulation value.

Appl. No. 10/820,500
Reply to Office action of December 26, 2007

Claim 31 (Previously Presented): The clock generating method of claim 29, wherein
the step of generating the modulated clock signal comprises:
receiving the oscillation clock signals and outputting at least two of them as
5 selection signals; and
generating the modulated clock signal according to the selection signals;
wherein at least one of the step of outputting the selection signals and the step of
generating the modulated clock signal according to the selection signals is
executed according to the modulation value.

10

Claims 32-39 (Cancelled)

Claim 40 (New): The clock generating circuit of claim 17, further comprising:
at least one spread spectrum clock signal generator, coupled to the spread
15 spectrum control circuit, for generating a spread spectrum clock signal in
accordance with the modulated clock signal;
wherein the spread spectrum clock signal, the output clock signal and the
modulated clock signal are separate signals.

20 Claim 41 (New): The clock generating method of claim 25, further comprising:
generating a spread spectrum clock signal in accordance with the modulated
clock signal;
wherein the spread spectrum clock signal, the output clock signal and the
modulated clock signal are separate signals.

25